

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
22 November 2001 (22.11.2001)

PCT

(10) International Publication Number
WO 01/87676 A2

(51) International Patent Classification⁷: **B60R 22/16**

Beacon Hill Court #308, Auburn Hills, MI 48326 (US).
GRAF, Robert; Innerpichl 30, I-39030 Pichl/Gsies (IT).

(21) International Application Number: PCT/US01/14946

(22) International Filing Date: 9 May 2001 (09.05.2001)

(74) Agents: **SLENZAK, Laura**; c/o Keller, Elsa, Siemens Corporation, 186 Wood Avenue South, Iselin, NJ 08830__ et al. (US).

(25) Filing Language: English

(81) Designated States (*national*): DE, GB, JP, KR.

(26) Publication Language: English

(84) Designated States (*regional*): European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR).

(30) Priority Data:

60/203,778	12 May 2000 (12.05.2000)	US
60/207,503	26 May 2000 (26.05.2000)	US

Published:

— without international search report and to be republished upon receipt of that report

(71) Applicant: **SIEMENS AUTOMOTIVE CORPORATION** [US/US]; 2400 Executive Hills Drive, Auburn Hills, MI 48326-2980 (US).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(72) Inventors: **CURTIS, Brian, M.**; 3285 Regency Drive, Orion, MI 48359 (US). **LICHTINGER, Harald**; 2648



WO 01/87676 A2

(54) Title: SEAT BELT FORCE SENSOR SYSTEM

(57) Abstract: A system for measuring seat belt forces is used to control deployment of vehicle airbags. The system includes a rigid plate member having one end attached to a portion of the seat belt and an opposite end mounted to a vehicle structure. The seat belt is used to secure passengers or an infant car seat to the vehicle seat. A sensor including a strain gage is mounted on the rigid plate between the ends and is used to measure the magnitude of forces exerted on the seat belt by the passenger or car seat. The strain gage generates a signal representative of the tension in the seat belt, which is used to control deployment of the airbag. The airbag is not deployed if the tension in the seat belt exceeds a predetermined limit.

SEAT BELT FORCE SENSOR SYSTEM

BACKGROUND OF THE INVENTION

1. Field of the Invention.

5 This invention relates to a method and apparatus for measuring the force applied to a seat belt. Specifically, a sensor arrangement is mounted on a rigid plate secured between a seat belt portion and a vehicle structure to provide accurate seatbelt force measurements.

10 2. Related Art.

Most vehicles include airbags and seatbelt restraint systems that work together to protect the driver and passengers from experiencing serious injuries due to high-speed collisions. It is important to control the deployment force of the airbags based on the size of the driver or the passenger. When an adult is seated on the vehicle seat, 15 the airbag should be deployed in a normal manner. If there is an infant seat secured to the vehicle seat then the airbag should not be deployed or should be deployed at a significantly lower deployment force. One way to control the airbag deployment is to monitor the weight of the seat occupant.

Current systems for measuring the weight of a seat occupant are complex and 20 expensive. One type of system uses pressure sensitive foil mats mounted within the seat bottom foam. Another system uses sensors placed at a plurality of locations within the seat bottom. The combined output from the mats or the sensors is used to determine the weight of the seat occupant. If the sensors become damaged or fail to operate for some reason, the system will not provide accurate seat weight 25, measurements and airbag deployment could occur under undesirable conditions.

Also mounting sensor systems within the seat can be difficult and time consuming. It is difficult to find mounting locations for each the sensors that will accommodate all of the various positions of a seated occupant while still providing accurate measurements. Further, shifting of the occupant on the seat can dislodge or 30 move the sensors out of their proper location. Because the sensors are mounted within

the seat bottom, it is difficult to reposition the sensors after the seat is installed in the vehicle.

Current sensor systems also can have difficulty determining whether an adult is belted to the seat or whether a child car seat is belted to the seat. When a child seat is secured to a seat with a seat belt, an excess force acts on the sensors mounted within the rear portion of the seat bottom, which interferes with accurate weight sensing. Over tightening of the seatbelt to securely hold the child seat in place, pulls the child seat down against the rear part of the seat bottom, causing the excessive force measured by the sensors. Due to this effect, the current weight sensing systems have difficulty in discerning between an adult belted to a seat and a child seat secured to the seat with a seat belt.

Thus, it is desirable to have a system for determining whether conditions are proper for deploying an airbag by determining whether a child seat or an adult is secured to the seat with a seat belt. The system should further work with traditional seat occupant weight sensing systems and should provide accurate measurements, be easy to install, and overcome the above referenced deficiencies with prior art systems.

SUMMARY OF THE INVENTION

A seat belt sensor system includes a load cell with a strain gage that is integrated into a seat belt mechanism that is used to secure an occupant to a vehicle seat. When the seat belt is tightened, the sensor is pulled into tension and this is measured by the strain gage. The strain gage measurements and signals are send to an electronics unit that processes the signals and feeds the signal back to an occupant sensing control unit. Occupant sensing control unit uses the information to determine whether a child seat or an adult is belted to the vehicle seat an ultimately controls the deployment of an airbag mechanism.

In a disclosed embodiment of this invention, the sensor assembly includes rigid member with a first end for supporting a seat belt portion and a second end for attachment to a vehicle structure, such as a B-pillar or seat mount, for example. The strain gage is mounted on the rigid member between the first and second ends and is used to measure the strain exerted on the rigid member by tension forces applied to the

seat belt portion. An electrical connector is also mounted to the rigid member next to the strain gage. The electrical connector receives the strain measurements and transmits the measurements to a central processor to determine the magnitude of the tension force.

5 Preferably the rigid member is formed as a metallic plate that is defined by a length, width, and thickness. The length is greater than the width and the thickness is significantly less than the length and the width. The rigid member includes a neck portion positioned between the first and second ends with the width being less than the width of the first and second ends. The strain gage is mounted on the neck
10 portion and measures the strain resulting from tension forces exerted on the first end of the rigid member by the seat belt.

 In a preferred embodiment, the sensor assembly is incorporated into an occupant sensing control system that controls deployment of safety devices such as an
15 airbag based on the tension forces measured in the seat belt. The strain gage generates a signal representative of the tension forces in the seat belt and transmits the signal to an electronic controller or processor. The airbag is prevented from deploying if the signal exceeds a predetermined limit.

 A method for controlling airbag deployment includes the following steps. The seat belt assembly is provided with a buckle strap attached to a male buckle member
20 and a seat belt latch mechanism with a female receptacle for receiving the male buckle member to secure the occupant to the vehicle seat. The rigid plate has one end secured to a portion of the seat belt and an opposite end of the plate is secured to a vehicle structure with a strain gage mounted to the rigid plate between the ends. The male buckle member is latched to the female receptacle and a tension force is generated on
25 the seat belt assembly by tightening the buckle strap. The strain is measured on the rigid plate due to the tension force with the strain gage. A tension force signal is generated based on strain measurement and deployment of an airbag is controlled based on the tension force signal.

 The airbag is not deployed if the tension in the seat belt exceeds a
30 predetermined limit. By measuring the tension in the seat belt a differentiation can be made between an adult belted to a seat and a child seat belted to the seat. Thus,

deployment of the airbag can be more effectively controlled and will not be deployed when a child seat is belted in place.

These and other features of the present invention can be best understood from the following specification and drawings, the following of which is a brief description.

5

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 is a schematic view showing a vehicle with an airbag system and an occupant sitting in a seat with the airbag in an active state shown in dashed lines.

Figure 2 is a schematic side view of a seat assembly with an infant car seat
10 secured to the vehicle seat.

Figure 3 is a schematic front view of a seat and seat belt assembly.

Figure 4 is an overhead view of subject sensor assembly.

Figure 5 is a side view of the sensor of Figure 4.

Figure 6 is schematic diagram of the control system.

Figure 7 is a perspective view of an alternate embodiment of the sensor
15 assembly.

Figure 8 is a side cross-sectional view of the sensor assembly mounted to a B-pillar.

Figure 9 is a perspective view of the sensor assembly of Figure 8.

Figure 10 is a perspective view, partially cut-away, of the sensor assembly
20 mounted in a seat latch mechanism.

DETAILED DESCRIPTION OF AN EXEMPLARY EMBODIMENT

A vehicle includes a vehicle seat assembly, shown generally at 12 in Figure 1,
25 and an airbag system 14. The seat assembly 12 is preferably a passenger seat and includes a seat back 16 and a seat bottom 18. A vehicle occupant 20 is secured to the seat 12 with a seatbelt 22. A tension force F_T is exerted on the seat belt 22. The tension force F_T represents the force is exerted against the occupant as the belt is tightened.

30 The airbag system 14 deploys an airbag 24 under certain collision conditions. The deployment force for the airbag 24, shown as deployed in dashed lines in Figure 1, varies depending upon the type of occupant that is belted to the seat 12. When an adult

20 is belted to the vehicle seat 12, the airbag 24 should be deployed in a normal manner shown in Figure 1. If there is an infant or child seat 26 secured to the vehicle seat 12, see Figure 2, then the airbag 24 should not be deployed. Thus, it is important to be able to determine whether there is an adult 20 belted to the seat 12 or whether an infant seat 26 is secured to the seat with a seat belt 22. One way to determine this is by monitoring the tension exerted on the seat belt 22. When an adult 20 is belted to the seat, normal seat belt forces are exerted against the seat belt 22. When an infant or child seat 26 is belted to the seat 12, high tension forces are exerted on the seat belt 22 because the seat belt 22 is overtightened to securely hold the child seat 26 in place.

The seat belt 22, shown more clearly in Figure 3, has a strap portion 28 that includes a shoulder harness and/or lap belt that is connected to a male buckle member 30. A seat belt latch mechanism 32 is hard mounted to the seat 12 and typically extends outwardly from the seat 12 between the seat back 16 and the seat bottom 18. The latch mechanism 32 includes a female receptacle 34 that receives the male buckle member 30 to secure the occupant 20 or child seat 26 to the seat 12. The strap portion 28 can be manually or automatically tightened once the belt is buckled to a desired tension.

A sensor assembly 40 for measuring the tension forces in the seat belt 22 is shown in Figures 4 and 5. The sensor assembly 40 includes a rigid member that is preferably formed as a metallic plate 42 from 4130Rc39 material, however, other similar materials could also be used. The plate 42 includes a first end 44 that is attached via a loop connection 46 to material that forms a portion of the seat belt 22 and a second end 48 that is attached to a vehicle structure. The vehicle structure attachment will be discussed in greater detail below.

The plate 42 is defined by a length "l", a width "w", and a thickness "t". In the preferred embodiment, the length l is greater than the width w and the thickness t is significantly less than the width w and the length l. The plate 42 includes a necked portion 50 positioned between the ends 44, 48 that is narrower than the ends 44, 48. A strain gage 52 is mounted on the necked portion 50. The tightening of the seat belt 22 exerts a tension force F_T on the plate 42 via the looped connection 46,

which results in strain on the necked portion 50. The strain gage 52 measures this strain. The strain gage 52 is preferably a full bridge strain gage with four (4) grids.

The first end 44 of the plate 42 is preferably positioned at an angle relative to the necked portion 50 and the second end 48. This causes the tension force to be applied at an angle, which creates a moment M_T at one edge of the necked portion 50. The second end 48 of the plate 42 is hard mounted to a vehicle structure creating a reaction force F_{rea} and moment M_{rea} . The strain gage 52 measures the strain resulting in the necked portion 50 of the plate 42 as the tension force F_T is applied to the first end 44 of the plate 42.

An electrical connector 54 is also mounted on the plate 42 adjacent to the strain gage 52. The strain measurements are generated as signals 56 that are sent from the gage 52 to the connector 54 and then to an electronic control unit (ECU) or microprocessor 58, see Figure 6. The ECU 58 can be incorporated into the connector 54 to include the necessary electronics and printed circuit board (as shown in Figure 4) or can be a separate component at a remote location on the vehicle. The ECU 58 processes the strain signals 56 to determine the magnitude of the tension forces F_T exerted on the seat belt 22 and sends a control signal 66 to a central electronic control unit (ECU) or central microprocessor 60 to control deployment of the airbag 24. It should be understood that the ECU 58 and the central ECU 60 could be separate units or could be the same unit. An optional configuration for an electrical connector 62 is shown in Figure 7. This configuration includes a simplified wire connection 64 to the ECU 58 and/or 60.

As discussed above, the plate 42 is hard mounted to a vehicle structure. The vehicle structure can be a B-pillar 68 as shown in Figures 8 and 9 or the seat latch mechanism 32 as shown in Figure 10. The B-pillar 68 extends vertically to one side of the vehicle and is typically positioned adjacent to the seat 12 and behind a front passenger door of the vehicle. The B-pillar mount includes a secondary metal plate 70 that includes a circular boss 72 for receiving a pivot pin 74 at one end 76. The opposite end 78 of the secondary metal plate 70 is mounted to the rigid metal plate 42 with at least one fastener 80.

The seat latch mechanism mount is shown in Figure 10. The second end 48 of the plate 42 includes at least one aperture 82 for receiving a fastener 84 to hard

mount the plate 42 to the seat. The opposite end 44 of the plate 42 has an elongated slot 86 for connecting the plate 42 to the looped material, which extends to the female receptacle 34 having a slot 88 for receiving the buckle member 30.

5 In both configurations, the strain gage 52 measure the strain caused by the tension force F_T in the seat belt 22. The airbag deployment is controlled based upon the strain measurements and the airbag 24 is not deployed if the tension force F_T exceeds a predetermined limit. An adult can experience a tension force in a seat belt up to approximately 30 pounds (lbs) and still be comfortable. If the strain gage 52 measures a tension force F_T that exceeds 30 lbs than that would indicate that a child
10 seat 26 has been belted to the seat 12. Thus, the airbag 24 would not be deployed during a collision under these conditions. It should be understood that 30 lbs is an approximate value, which can vary due to differing seat and seatbelt configurations. Thus, the predetermined limit for comparison to the measured tension force F_T can also vary depending upon the seat configuration.

15 The subject sensing system provides simplified and efficient apparatus and method for determining whether conditions are proper for deploying an airbag 24 by measuring seatbelt forces to discern whether a child in a child seat 26 or an adult is belted to the seat 12. The system provides accurate measurements and is easy to install.

20 Although a preferred embodiment of this invention has been disclosed, it should be understood that a worker of ordinary skill in the art would recognize many modifications come within the scope of this invention. For that reason, the following claims should be studied to determine the true scope and content of this invention.

CLAIMS

1. A sensor assembly for measuring seatbelt forces comprising:
a rigid member having a first end for supporting a seat belt portion and
5 a second end for attachment to a vehicle structure;
a strain gage mounted on said rigid member between said first and
second ends for measuring the strain exerted on said rigid member by a tension force
applied to the seat belt portion; and
an electrical connector mounted to said rigid member adjacent to said
10 strain gage for receiving strain measurements from said strain gage and transmitting
said measurements to a central processor to determine the magnitude of the tension
force.
2. An assembly according to claim 1 wherein said rigid member is a
15 metallic plate defined by a length, width, and thickness with said length being greater
than said width and said thickness being significantly less than said length and said
width.
3. An assembly according to claim 1 wherein said rigid member
20 includes a neck portion positioned between said first and second ends having a width
that is less than the width of said first and second ends and wherein said strain gage
is mounted on said neck portion.
4. An assembly according to claim 3 wherein said first end includes an
25 elongated slot for a loop attachment to the seat belt portion and said second end
includes at least one aperture for receiving a fastener for attachment to the vehicle
structure.
5. An assembly according to claim 4 wherein said electrical connector is
30 mounted to said rigid member adjacent to said second end between said aperture and
said neck portion.

6. A sensor system for controlling airbag deployment comprising:
a seat belt for securing an occupant to a vehicle seat;
a rigid plate having a first end for supporting a portion of said seat belt
and a second end for attachment to a vehicle structure;
5 a strain gage mounted on said rigid plate between said first and second
ends for measuring the strain exerted on said rigid plate by a tension force applied to
said seat belt;
an electrical connector mounted to said rigid plate adjacent to said
strain gage for receiving strain measurements from said strain gage and transmitting
10 said measurements to a processor to determine the magnitude of the tension force
wherein said processor generates a force signal representative of the magnitude of said
forces; and
an airbag mounted adjacent to the vehicle seat wherein airbag
deployment is controlled based on said force signal.
15
7. A system according to claim 6 wherein said airbag does not deploy
when said force signal exceeds a predetermined limit.
8. A system according to claim 7 wherein said rigid plate includes a
20 neck portion positioned between said first and second ends having a width that is
less than the width of said first and second ends and wherein said strain gage is
mounted on said neck portion.
9. A system according to claim 8 wherein said vehicle structure is a B-
25 pillar extending vertically adjacent to one side of said seat.
10. A system according to claim 9 including a secondary plate having a
first end pivotally mounted to said B-pillar and a second end rigidly attached to said
second end of said rigid member.
30

11. A system according to claim 10 wherein said first end of said rigid plate includes an elongated slot for a loop attachment to said portion of said seat belt and said second end of said rigid plate includes at least one aperture aligned with a corresponding aperture in second end of said secondary plate for receiving a fastener
5 for attachment to attach said rigid plate to said secondary plate.

12. A system according to claim 11 wherein said first end of said secondary plate includes a circular boss for receiving a pivot pin.

10 13. A system according to claim 8 wherein said vehicle structure is a seat mount for a seat belt buckle latch mechanism.

14. A system according to claim 13 wherein said seat belt includes a buckle strap for supporting a male buckle member and said seat belt buckle latch mechanism
15 includes a female receptacle for receiving said male buckle member to securely latch the occupant to said seat with said portion of said seat belt extending between said male receptacle and said rigid plate.

15. A method for controlling airbag deployment comprising the steps of
20 providing a seat belt assembly having a buckle strap attached to a male buckle member, a seat belt latch mechanism having a female receptacle for receiving the male buckle member to secure an occupant to a vehicle seat, and a rigid plate having one end secured to a portion of the seat belt and an opposite end secured to a vehicle structure with a strain gage mounted to the rigid plate between the ends;
25 latching the male buckle member to the female receptacle
generating a tension force on the seat belt assembly by tightening the buckle strap;
measuring the strain on the rigid plate due to the tension force with the strain gage;
30 generating a tension force signal based on strain measurement; and
controlling deployment of an airbag based on the tension force signal.

16. A method according to claim 17 including the step of preventing deployment of the airbag if the tension force signal exceeds a predetermined limit.

17. A method according to claim 16 including the step of mounting the
5 rigid plate to a B-pillar.

18. A method according to claim 16 including the step of mounting the rigid plate to a seat mount.

10 19. A method according to claim 16 including the step of mounting an electrical connector on the rigid plate adjacent to the strain gage to receive the strain measurement and transmit the measurement to a processor.

1/5




Fig-1




Fig-2

2/5




Fig-3




Fig-4

3/5




Fig-5




Fig-6




Fig-7

┐




Fig-8




Fig-9




Fig-10

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau




(43) International Publication Date
22 November 2001 (22.11.2001)

PCT

(10) International Publication Number
WO 01/87676 A3

- (51) International Patent Classification⁷: **B60R 22/18**, G01L 5/10
- (21) International Application Number: PCT/US01/14946
- (22) International Filing Date: 9 May 2001 (09.05.2001)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
60/203,778 12 May 2000 (12.05.2000) US
60/207,503 26 May 2000 (26.05.2000) US
- (71) Applicant: **SIEMENS AUTOMOTIVE CORPORATION** [US/US]; 2400 Executive Hills Drive, Auburn Hills, MI 48326-2980 (US).
- (74) Agents: **SLENZAK, Laura**; c/o Keller, Elsa, Siemens Corporation, 186 Wood Avenue South, Iselin, NJ 08830 et al. (US).
- (81) Designated States (*national*): DE, GB, JP, KR.
- (84) Designated States (*regional*): European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR).
- Published:
— with international search report
— before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments
- (88) Date of publication of the international search report:
27 June 2002
- (72) Inventors: **CURTIS, Brian, M.**; 3285 Regency Drive, Orion, MI 48359 (US). **LICHTINGER, Harald**; 2648 Beacon Hill Court #308, Auburn Hills, MI 48326 (US). **GRAF, Robert**; Innerpichl 30, I-39030 Pichl/Gsies (IT).
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: SEAT BELT FORCE SENSOR SYSTEM



(57) Abstract: A system for measuring seat belt forces is used to control deployment of vehicle airbags. The system includes a rigid plate member having one end attached to a portion of the seat belt and an opposite end mounted to a vehicle structure. The seat belt is used to secure passengers or an infant car seat to the vehicle seat. A sensor including a strain gage is mounted on the rigid plate between the ends and is used to measure the magnitude of forces exerted on the seat belt by the passenger or car seat. The strain gage generates a signal representative of the tension in the seat belt, which is used to control deployment of the airbag. The airbag is not deployed if the tension in the seat belt exceeds a predetermined limit.

WO 01/87676 A3

INTERNATIONAL SEARCH REPORT

International Application No

PC./US 01/14946

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 B60R22/18 G01L5/10

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 B60R G01L

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, PAJ

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
P,X P,Y	DE 100 49 528 A (TAKATA CORP) 12 April 2001 (2001-04-12) abstract; figures 1,3,5 page 7, line 25 -page 8, line 19	1,2,6,7, 15,16,19 17,18
Y	US 5 996 421 A (HUSBY HARALD SNORRE) 7 December 1999 (1999-12-07) figures 1-6 abstract column 2, line 42 -column 4, line 49	17
P,Y	PATENT ABSTRACTS OF JAPAN vol. 2000, no. 13, 5 February 2001 (2001-02-05) & JP 2000 302004 A (TOYOTA MOTOR CORP), 31 October 2000 (2000-10-31) abstract	18
-/--		

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *Z* document member of the same patent family

Date of the actual completion of the international search

10 April 2002

Date of mailing of the international search report

17/04/2002

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040. Tx. 31 651 epo nl.
Fax: (+31-70) 340-3016

Authorized officer

D'sylva, C

INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 01/14946

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
P,X	DE 199 48 661 C (BAYERISCHE MOTOREN WERKE AG) 25 January 2001 (2001-01-25)	1,2,6
P,Y	figures 1,2 abstract column 2, line 65 -column 3, line 35	7,15-19
Y	WO 99 29538 A (AUTOMOTIVE SYSTEMS LAB) 17 June 1999 (1999-06-17) figures 1,2 abstract page 6, line 4 -page 7, line 19	7,15-19
A	PATENT ABSTRACTS OF JAPAN vol. 014, no. 157 (M-0955), 27 March 1990 (1990-03-27) & JP 02 018135 A (MAZDA MOTOR CORP), 22 January 1990 (1990-01-22) abstract	1-6,15
A		7,15
A	WO 99 12012 A (BREED AUTOMOTIVE TECH) 11 March 1999 (1999-03-11) figure 5 abstract page 9, line 19 -page 10, line 2	1-9, 15-17,19
A	US 2 513 295 A (PHILLIP EISENBERG) 4 July 1950 (1950-07-04) figures 1,2 column 1, paragraphs 1,2 column 1, line 34 -column 2, line 42	1-6

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 01/14946

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
DE 10049528	A	12-04-2001	JP 2001171480 A DE 10049528 A1 GB 2357361 A	26-06-2001 12-04-2001 20-06-2001
US 5996421	A	07-12-1999	WO 9955559 A1	04-11-1999
JP 2000302004	A	31-10-2000	EP 1020320 A2 US 6356200 B1	19-07-2000 12-03-2002
DE 19948661	C	25-01-2001	DE 19948661 C1	25-01-2001
WO 9929538	A	17-06-1999	US 6205868 B1 CA 2311299 A1 EP 1035990 A1 JP 2002500977 T WO 9929538 A1	27-03-2001 17-06-1999 20-09-2000 15-01-2002 17-06-1999
JP 02018135 4	A		NONE	
WO 9912012	A	11-03-1999	WO 9912012 A1	11-03-1999
US 2513295	A	04-07-1950	NONE	